

3082A Paired - DeviceBus® for ODVA DeviceNet™

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

15 and 18 AWG stranded tinned copper conductors, PVC insulation (power), FPE insulation (data), individually foil shielded (100% coverage) plus an overall tinned copper braid (65% coverage), sunlight/oil-resistant PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	2
Total Number of Conductors	4

AWG :

Number of Pairs	AWG	Stranding	Conductor Material	Conductor Diameter (in.)
1	15	19x28	TC - Tinned Copper	
1	18	19x30	TC - Tinned Copper	

Stranding	19x28, 19x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride, FPE - Foam Polyethylene
---------------------	---

Insulation Material (Multi-AWG) :

AWG	Layer Number	Material Trade Name	Material	Wall Thickness (in.)	Diameter (in.)
15			PVC - Polyvinyl Chloride		
18			FPE - Foam Polyethylene		

Pair Color Code Chart :

Number	Color	Number	Color
1 (15 AWG)	Red & Black	2 (18 AWG)	Blue & White

INNER SHIELD:

Inner Shield Type	Tape/Tape
-------------------	-----------

Inner Shield Material :

Layer Number/Description	Material Trade Name	Type	Material	% Coverage (%)	Stranding	Diameter (in.)	Conductor Material
15 AWG Pair		Tape	Aluminum Foil-Polyester Tape	100			
18 AWG Pair		Tape	Aluminum Foil-Polyester Tape	100			

3082A Paired - DeviceBus® for ODVA DeviceNet™

Inner Shield % Coverage	100 %
-------------------------	-------

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	TC - Tinned Copper
Outer Shield % Coverage	65 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	18
Outer Shield Drain Wire Stranding	19x30
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.060 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.480 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C (UL AWM Style 20201)
Bulk Cable Weight	108 lbs/1000 ft.
Max. Recommended Pulling Tension	190 lbs.
Min. Bend Radius (Install)	4.6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG, PLTC-ER
CEC/C(UL) Specification	CMG
AWM Specification	UL Style 20201 (600 V 75°C)
CSA Specification	I/II A
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
Other Specification	ODVA Class 2 Thick

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
CSA Flame Test	FT4

SUITABILITY:

Sunlight Resistance	Yes
Oil Resistance	Yes

3082A Paired - DeviceBus® for ODVA DeviceNet™

PLENUM/NON-PLENUM:

Plenum (Y/N) N

ELECTRICAL CHARACTERISTICS:

Unaveraged Impedance :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Unaveraged Impedance (Ohms)
18 AWG Pair Only				120

Nom. Inductance :

Description	Nom. Inductance (μH/ft)
15 AWG Pair Only	.174

Nom. Capacitance Conductor to Conductor :

Description	Frequency (kHz)	Start Frequency (kHz)	Stop Frequency (kHz)	Nom. Capacitance Conductor to Conductor (pF/ft)
18 AWG Pair Only	1			12.0

Nominal Velocity of Propagation :

Description	Nominal Velocity of Propagation (%)
18 AWG Pair Only	75

Maximum Delay :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Delay (ns/ft)
18 AWG Pair Only				1.36

Nom. Conductor DC Resistance @ 20 Deg. C :

Description	Nom. Conductor DC Resistance @ 20 Deg. C (Ohms/1000 ft)
15 AWG	3.6
18 AWG	6.9

Nominal Outer Shield DC Resistance @ 20 Deg. C 1.8 Ohms/1000 ft

Max. Attenuation (dB/100 ft.) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 ft.)
18 AWG Pair Only	.125			.13
	.500			.25
	1.00			.40

Max. Operating Voltage - UL :

UL Voltage	Description
300 V RMS	C(UL) AWM

Max. Recommended Current :

Description	Max. Recommended Current
15 AWG	8.0 Amps
18 AWG	5.0 Amps

NOTES:

Notes

Thick. Meter marks on jacket to aid users in installation. ODVA DeviceNet is an Open DeviceNet Vendor Associatio, Inc. Trademark.

3082A Paired - DeviceBus® for ODVA DeviceNet™

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
3082A 0021000	2 #15, 2 #18 SHLD FRPVC	1000	138	RED	C
3082A T5U1000	2 #15, 2 #18 SHLD PVC	1000	138	GRAY T5U	C
3082A T5U2000	2 #15, 2 #18 SHLD PVC	2000	280	GRAY T5U	C
3082A T5U500	2 #15, 2 #18 SH PVC	500	71	GRAY T5U	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 02-22-2007

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.